Kerstar

KV 20, 25, 30, 45 & 50 Wet & Dry Vacuum Cleaners

Built without compromise to offer years of reliable service, this versatile range of industrial wet and dry vacuum cleaners will happily take on the toughest jobs. There is a model in this range perfectly suited to most requirements. The KV range can be supplied with a dent proof injection-moulded or non-magnetic stainless steel canister, a four castor chassis or heavy duty tubular caddy, and a choice of single or double motors on all sizes of canister. The KV 50 features the extra advantage of pivoting tip action to make it easy to empty.

FEATURES

Wet and Dry

- Twin fan bypass cooling motor
- One or two motors
- Thermal switch protection against overheating
- Virtually indestructible thick section injection moulded plastic motor head
- KV 30, 45 & 50 can be fitted with our bolt on fixed floor tool
- Hose entry will accept 32, 38 & 51mm hose and tool kits
- Non-magnetic 304 grade stainless steel canister or dent proof plastic canister
- Four castor chassis or tubular caddy for rougher surfaces
- Antistatic hose entry and 38mm conductive tool kit to dissipate build-up of nuisance static (Available for models with stainless steel canister at time of order or as a retro fit).

Wet only

- Efficient float ball wet shut off
- Net filter to float cage to prevent motor damage
- KV 30 & 45 can be fitted with dump valve or drain hose and stopper for quicker wet emptying.

Dry only

- Two stage dry filtration disposable paper bag/filter and high efficiency cloth filter
- Optional high efficiency cloth filter.







TECHNICAL SPECIFICATION

	KV 20	KV 25	KV 30	KV 45	KV 50
DIMENSIONS (h x w x d)	610x440x440mm	625x440x440mm	865x450x460mm	865x450x460mm	920x520x560mm
WEIGHT	Single 13.5kg	Single 12.5kg	Single 16.8kg	Single 17.8kg	Single 19kg
	Twin 16.25kg	Twin 15.25kg	Twin 19.7kg	Twin 20.7kg	Twin 22kg
MOTOR	Single 1000w Max 800w Mean				
	Twin 2000w Max 1600w Mean				
POWER	230/110v or 50/60Hz				
PERFORMANCE	Single Max Airflow - 156m³/Hr				
	Twin Max Airflow - 295m³/Hr				
CAPACITY WET/ DRY LITRES	14/20l	18/23l	24/30l	34/40l	34/40l
CLEANING RANGE	28.5m/94ft	28.5m/94ft	28.5m/94ft	28.5m/94ft	28.5m/94ft

Max Vacuum single & twin motors 2200mm











KV 20, 25, 30, 45 and 50